

US009409541B2

US 9,409,541 B2

Aug. 9, 2016

(12) United States Patent Burry et al.

(54) INTERIOR TRIM PART FOR A MOTOR VEHICLE COMPRISING AN AIRBAG DOOR

(71) Applicants: Charles Burry, Angy (FR); Daniel Ory,

Le Plessis Bouchard (FR)

(72) Inventors: Charles Burry, Angy (FR); Daniel Ory,

Le Plessis Bouchard (FR)

(73) Assignee: Faurecia Interieur Industrie, Nanterre

(FR)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 14/526,063

(22) Filed: Oct. 28, 2014

(65) Prior Publication Data

US 2015/0151706 A1 Jun. 4, 2015

(30) Foreign Application Priority Data

(51) Int. Cl.

B60R 21/20 (2011.01)

B60R 21/2165 (2011.01)

B29C 44/34 (2006.01)

B60R 21/205 (52) U.S. Cl.

CPC *B60R 21/2165* (2013.01); *B29C 44/351* (2013.01); *B60R 21/205* (2013.01)

(2011.01)

(58) Field of Classification Search

CPC B60R 21/20; B60R 21/205; B60R 21/21506; B60R 2021/21506

See application file for complete search history.

. .

(10) **Patent No.:**

(56)

(45) **Date of Patent:**

References Cited U.S. PATENT DOCUMENTS

5,533,749	A *	7/1996	Leonard B29C 59/007
6,250,669	B1 *	6/2001	280/728.3 Ohmiya B60R 21/205
6,322,101	B1*	11/2001	280/728.2 Suizu B60R 21/2165
6,854,783	B2*	2/2005	280/728.3 Teranishi B60K 37/00
			296/37.12

(Continued)

FOREIGN PATENT DOCUMENTS

DE 102008011697 A1 9/2009 JP 2006306230 A 11/2006 (Continued)

OTHER PUBLICATIONS

Search report for related French Application No. 13 62068; report dated Jun. 10, 2014.

Primary Examiner — James English

(74) Attorney, Agent, or Firm — Miller, Matthias & Hull LLP

(57) ABSTRACT

Interior trim part for a motor vehicle comprising a body, a channel-door assembly, a sealing system and a foam layer. The body comprises a passage. The channel-door assembly is mounted on the body. The channel-door assembly comprises a channel wall and a door portion. The channel wall has an inner surface and an outer surface, the inner surface being intended to guide the deployment of an airbag, the outer surface extending along a deployment direction. The door portion is connected to the channel wall and overlies the passage. The sealing system extends around the outer surface of the channel wall, in continuous contact with the body and comprises a lip protruding from the outer surface of the channel wall. The foam layer covers the body and the door portion.

9 Claims, 2 Drawing Sheets

